



## PV Connectors

### PV-Stick with SNAP IN connection

No crimping tool, no lost time, no extra effort - the unique PV-Stick uses tried-and-tested SNAP IN technology. The fastest, easiest and safest way to wire up photovoltaic plants - literally in no time.

### PV-Stick - Photovoltaic connectors - SNAP IN connection

Type	Rated voltage (IEC) Rated current	Connection cross-section min. / max.	Continuous operating temperature min. / max.	Qty.	Order No.
<b>Socket</b>					
PV-STICK+ Qty.10	1500 V DC / 30 A	4 / 6 mm <sup>2</sup>	-40 °C...+85 °C	10	1303450000
PV-STICK+ Qty.50	1500 V DC / 30 A	4 / 6 mm <sup>2</sup>	-40 °C...+85 °C	50	1303460000
PV-STICK+ Qty.200	1500 V DC / 30 A	4 / 6 mm <sup>2</sup>	-40 °C...+85 °C	200	1303470000
<b>Pin</b>					
PV-STICK- Qty.10	1500 V DC / 30 A	4 / 6 mm <sup>2</sup>	-40 °C...+85 °C	10	1303490000
PV-STICK- Qty.50	1500 V DC / 30 A	4 / 6 mm <sup>2</sup>	-40 °C...+85 °C	50	1303500000
PV-STICK- Qty.200	1500 V DC / 30 A	4 / 6 mm <sup>2</sup>	-40 °C...+85 °C	200	1303510000
<b>PV-Stick Set</b>					
PV-STICK SET	1500 V DC / 30 A	4 / 6 mm <sup>2</sup>	-40 °C...+85 °C	1	1422030000



### Accessories

Type	Description	Qty.	Order No.
SAFETY-CLIP WM4 Qty.10	Locking clip for PV-Stick prevents opening without tools	10	1328150000
VSSO WM4 C	Sealing cap for protecting PV connectors that are not mated (all connectors)	100	1254870000



### Wire stripping tool

Type	Cutting	Stripping	Qty.	Order No.
MULTI-STRIPAX PV	2,5, 4,0 and 6 mm <sup>2</sup>	2,5, 4,0 and 6 mm <sup>2</sup>	1	1190490000



### Wire cutting tool

Type	Maximum cutting performance	Copper finely stranded	Aluminium stranded	Qty.	Order No.
KT 12	25 mm <sup>2</sup>	35 mm <sup>2</sup>	16 mm <sup>2</sup>	1	9002660000

